

Amendment, October 20, 2004

PCT/EP03/01950

5 Faurecia Innenraum Systeme GmbH F02036

017P 6967

New patent claims 1 - 13

- 10 1. Motor vehicle (2) having a face wall (1) and a
brake booster (5) secured to this face wall, the
face wall having a first wall (3a) and a second
wall (3b) at a spacing from same,
characterised in that
- 15 for sound-proofing, the first wall has a recess
(4) to accommodate a brake booster (5) secured
solely to the first wall, and the brake booster
is only secured to the first wall.
- 20 2. Motor vehicle according to claim 1, **character-**
ised in that an edge region (6) of the recess
(4) is reinforced.
- 25 3. Motor vehicle according to claim 2, **character-**
ised in that the brake booster (5) has an edge
surface (7) which rests on an edge region (6) of
the recess (4).
- 30 4. Motor vehicle according to claim 3, **character-**
ised in that an elastomer ring (8) is arranged
on the edge surface (7) of the brake booster (5)
on the side oriented towards the edge region
(6).
5. Motor vehicle according to one of the preceding
claims, **characterised in that** the brake booster
(5) is screwed to the first wall (3a).

6. Motor vehicle according to one of the preceding claims, **characterised in that** the second wall (3b) has a feed-through aperture (10) for the brake booster (5).
- 5 7. Motor vehicle according to claim 6, **characterised in that** the gap (11) between the feed-through aperture (10) and brake booster (5) is between 1 mm and 20 mm, preferably between 1 mm and 5mm, in the region of the feed-through aperture.
10
8. Motor vehicle according to one of claims 6 or 7, **characterised in that** the face wall (1) has curvatures in the region of the recess (4) and/or the feed-through aperture (10).
- 15 9. Motor vehicle according to one of the preceding claims, **characterised in that** the face wall (1) has reinforcing webs in the region of the recess (4).
- 20 10. Motor vehicle according to one of the preceding claims, **characterised in that** foam (12) is arranged between the first wall (3a) and the second wall (3b).
- 25 11. Motor vehicle according to one of the preceding claims, **characterised in that** the brake booster is covered on its outer surface (13) with a foam-repelling material.
- 30 12. Motor vehicle according to one of the preceding claims, **characterised in that** the face wall (1) is designed as a module for mounting in a face wall frame (14) of the body of a motor vehicle.
13. Motor vehicle according to one of the preceding

claims, **characterised in that** the first wall (3a) and/or the second wall (3b) are/is formed from plastics material or metal.